## NSN 5320-01-391-2315

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-391-2315



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.760 inches and 0.780 inches

### Head Style:

Err-090

#### Head Height:

Between 0.010 inches and 0.015 inches

## Width Between Flats:

Between 0.122 inches and 0.142 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Head Minor Diameter:

Between 0.375 inches and 0.388 inches

## **Countersink Height:**

Between 0.0600 inches and 0.0625 inches

#### Lubrication:

Solid film and cetyl alcohol

#### **End Application:**

C-17

## Grip Length:

Between 0.370 inches and 0.380 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

#### **Countersink Angle:**

100.0 degrees

## **Product Name:**

Pin-rivet, threaded

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams4967 assn standard single material response or ams4928 assn standard single material response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-391-2315

Pin-rivet - Page 2 of 2

Specification Data:

88277-3d0098 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

