# NSN 5320-01-391-2323

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-391-2323



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.785 inches and 1.805 inches

## Head Style:

Err-090

#### Head Height:

Between 0.1308 inches and 0.1329 inches

## Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.672 inches and 0.684 inches

## Grip Length:

Between 1.245 inches and 1.255 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Thread Size:

0.375 inches

## Shear Strength:

95000 single pounds per square inch

## **Special Features:**

Kal-gard fa or em620c, solid film lube per mil-l-8937

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A528u0