

View Online at <https://aerobasegroup.com/nsn/5320-01-391-2333>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.063 inches and 2.083 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.1510 inches and 0.1540 inches

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.772 inches and 0.797 inches

**Grip Length:**

Between 1.433 inches and 1.443 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.4375 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Kal-gard fa or em620c, solid film lube per mil-I-8937

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0