# NSN 5320-01-391-2810

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-391-2810



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.348 inches and 1.368 inches

### Head Style:

Err-090

#### Head Height:

Between 0.010 inches and 0.015 inches

### Width Between Flats:

Between 0.197 inches and 0.217 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

#### Head Minor Diameter:

Between 0.541 inches and 0.554 inches

## **Countersink Height:**

Between 0.770 inches and 0.795 inches

### Lubrication:

Cetyl alcohol and solid film

### **End Application:**

C-17

### Grip Length:

Between 0.808 inches and 0.818 inches

### Thready Qty Per Inch (tpi):

24

### Thread Size:

0.375 inches

#### **Countersink Angle:**

100.0 degrees

### **Product Name:**

Pin-rivet, threaded

## Material:

Titanium alloy uns r56400

# Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-391-2810

Pin-rivet - Page 2 of 2

Specification Data:

88277-3d0098 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

