

View Online at <https://aerobasegroup.com/nsn/5320-01-391-2810>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.348 inches and 1.368 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.010 inches and 0.015 inches

**Width Between Flats:**

Between 0.197 inches and 0.217 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.5554 inches and 0.5604 inches

**Head Minor Diameter:**

Between 0.541 inches and 0.554 inches

**Countersink Height:**

Between 0.770 inches and 0.795 inches

**Lubrication:**

Cetyl alcohol and solid film

**End Application:**

C-17

**Grip Length:**

Between 0.808 inches and 0.818 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet, threaded

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4967 assn standard single material response or ams4928 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

88277-3d0098 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0