
## NSN 5320-01-391-2833

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.440 inches and 1.460 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.104 inches and 0.119 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### Lubrication:

Solid film and cetyl alcohol

## End Application:

C-17

#### Grip Length:

Between 1.120 inches and 1.130 inches

#### Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.190 inches

#### Shear Strength:

5380 double pounds per square inch

#### **Product Name:**

Pin-rivet, threaded

#### Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a



# NSN 5320-01-391-2833

Pin-rivet - Page 2 of 2



---

Demilitarization:

No

Fiig:

A528u0

