

View Online at <https://aerobasegroup.com/nsn/5320-01-391-2838>

Fastener Length:

Between 1.320 inches and 1.400 inches

Head Style:

Flat fillister w/protruding stud

Head Height:

0.0815 inches

Shank Diameter:

0.2885 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.494 inches

Lubrication:

Dry film or cetyl alcohol or paraffin wax

Grip Length:

Between 0.350 inches and 0.400 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

95000 pounds per square inch

Special Features:

Dry film lubricant is prohibited on the exposed paintable surfaces of the nut head; drive nut brown in color

Heat Treatment:

Annealed sleeve

Material:

Titanium alloy uns r56400 nut

Material Specification:

Mil-t-9047 military specification single material response nut or ams4928 assn standard single material response nut or ams4967 assn standard single material response nut

Surface Treatment:

Phosphate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response bolt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-t-9047 spec.