

View Online at <https://aerobasegroup.com/nsn/5320-01-391-2838>

**Fastener Length:**

Between 1.320 inches and 1.400 inches

**Head Style:**

Flat fillister w/protruding stud

**Head Height:**

0.0815 inches

**Shank Diameter:**

0.2885 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.494 inches

**Lubrication:**

Dry film or cetyl alcohol or paraffin wax

**Grip Length:**

Between 0.350 inches and 0.400 inches

**Features Provided:**

Drive nut

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Special Features:**

Dry film lubricant is prohibited on the exposed paintable surfaces of the nut head; drive nut brown in color

**Heat Treatment:**

Annealed sleeve

**Material:**

Titanium alloy uns r56400 nut

**Material Specification:**

Mil-t-9047 military specification single material response nut or ams4928 assn standard single material response nut or ams4967 assn standard single material response nut

**Surface Treatment:**

Phosphate nut

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response bolt

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-t-9047 spec.