## NSN 5320-01-391-3662

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-3662 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Orange **Fastener Length:** Between 0.765 inches and 0.785 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.375 inches and 0.380 inches Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** se

Ams 5662 assn standard single material respons
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-391-3662

Pin-rivet - Page 2 of 2



Fiig:

A528u0