

View Online at <https://aerobasegroup.com/nsn/5320-01-391-4342>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.737 inches and 2.757 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.269 inches and 0.289 inches

Shank Diameter:

Between 0.4990 inches and 0.4995 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

End Application:

C-17

Grip Length:

Between 2.058 inches and 2.068 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

37300 double pounds per square inch

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response or ams 4928 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0