# NSN 5320-01-391-4344

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-4344

#### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.385 inches and 2.405 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.200 inches and 0.210 inches

#### Width Between Flats:

Between 0.306 inches and 0.326 inches

#### Shank Diameter:

Between 0.5610 inches and 0.5615 inches

#### Shank Style:

Head Major Diameter:

Between 0.842 inches and 0.877 inches

#### Lubrication:

Solid film and cetyl alcohol

#### **End Application:**

C-17

#### Grip Length:

Between 1.620 inches and 1.630 inches

#### Thready Qty Per Inch (tpi):

18

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.5625 inches

#### Shear Strength:

57200 double pounds per square inch

#### **Product Name:**

Pin-rivet, threaded

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4867 assn standard single material response or ams 4928 assn standard single material response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-01-391-4344

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

