## NSN 5320-01-391-4349

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-391-4349



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.4475 inches and 2.4675 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.200 inches and 0.210 inches

## Width Between Flats:

Between 0.306 inches and 0.326 inches

#### Shank Diameter:

Between 0.5610 inches and 0.5615 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.842 inches and 0.877 inches

## Lubrication:

Solid film and cetyl alcohol

## **End Application:**

C-17

#### Grip Length:

Between 1.6825 inches and 1.6925 inches

## Thready Qty Per Inch (tpi):

18

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.5625 inches

## Shear Strength:

47200 double pounds per square inch

#### **Product Name:**

Pin-rivet, threaded

#### Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-391-4349

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

