## NSN 5320-01-391-5430

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-5430 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.550 inches and 2.570 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.220 inches and 0.224 inches **Shank Diameter:** 0.499 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 1.870 inches and 1.880 inches Min. Tensile Strength (psi): 343000 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 491000 double pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-391-5430

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0