

View Online at <https://aerobasegroup.com/nsn/5320-01-391-5496>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Blue

**Fastener Length:**

Between 0.552 inches and 0.572 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.1630 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.325 inches and 0.330 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.245 inches and 0.255 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.164 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Grit blast top of head

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0