## NSN 5320-01-391-5507

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-5507

Thread Class:

A3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.325 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

1.000 inches

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.1825 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Furnished w/ undersized thd dia

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-391-5507

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

