NSN 5320-01-391-5508

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-5508 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 0.697 inches and 0.717 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.501 inches and 0.506 inches **Grip Length:** Between 0.307 inches and 0.317 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Hi-shear specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-391-5508

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0