NSN 5320-01-391-7853

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-391-7853

| View Online at https://aerobasegroup.com/nsn/5320-01-391-7853 |
|---|
| Fastener Length: |
| Between 0.529 inches and 0.559 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Hole Diameter: |
| Between 0.152 inches and 0.162 inches |
| Shank Diameter: |
| Between 0.1883 inches and 0.1893 inches |
| Shank Style: |
| Tubular |
| Head Major Diameter: |
| Between 0.350 inches and 0.360 inches |
| Hole Depth: |
| Between 0.166 inches and 0.176 inches |
| Grip Length: |
| Between 0.435 inches and 0.465 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Heat Treatment: |
| Annealed |
| Material: |
| Steel comp 303se or steel comp 305 |
| Material Specification: |
| Ams5641 assn standard single material response or qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Specification Data: |
| 88277-s4932183 manufacturers standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |