# NSN 5320-01-391-7927

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-7927

### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.219 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.312 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

0.719 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.304 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Furnished w/ undersized thd dia; grit blast top of head, w/ color light blue on thd end

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-391-7927

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

