NSN 5320-01-391-7934

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-7934 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 2.365 inches and 2.385 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.127 inches and 0.129 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.628 inches and 0.633 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.870 inches and 1.880 inches Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 14600 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-391-7934

Pin-rivet - Page 2 of 2



Fiig:

A528u0