# NSN 5320-01-391-9150

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-391-9150



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Identification Code Color:

Blue

#### Fastener Length:

Between 2.865 inches and 2.885 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 2.370 inches and 2.380 inches

### Min. Tensile Strength (psi):

9200 pounds per square inch

#### Thread Size:

0.312 inches

#### Shear Strength:

14600 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Grit blast top of head, with color light blue on thread end.

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

# **Thread Series Designator:**

Unjf

## Specification Data:

73197-hlt453 manufacturers standard

## Shelf Life:

N/a

# NSN 5320-01-391-9150

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

