## NSN 5320-01-391-9153

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-9153 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Orange **Fastener Length:** Between 0.565 inches and 0.585 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.296 inches and 0.301 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** Between 0.245 inches and 0.255 inches Min. Tensile Strength (psi): 2600 pounds per square inch **Thread Size:** 0.188 inches **Shear Strength:** 7060 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-391-9153

Pin-rivet - Page 2 of 2



Fiig:

A528u0