## NSN 5320-01-391-9609

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-9609 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.6275 inches and 1.6475 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3765 inches and 0.3813 inches Lubrication: Solid film and cetyl alcohol **End Application:** C-17 **Grip Length:** Between 1.3075 inches and 1.3175 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-391-9609

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0