NSN 5320-01-391-9658

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-9658 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.122 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4990 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.438 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.4905 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Furnished w/ undersized thd dia; grip blast top of head, color light blue on thd endit blast top Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-391-9658

Pin-rivet - Page 2 of 2



Fiig:

A528u0