## NSN 5320-01-391-9664

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-9664 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 3.597 inches and 3.617 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.158 inches and 0.161 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.755 inches and 0.760 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 3.057 inches and 3.067 inches Min. Tensile Strength (psi): 14000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 21000 single pounds per square inch **Countersink Angle:** 100.09 degrees **Special Features:** Grit blast top of head Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-391-9664

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0