
## NSN 5320-01-391-9665

Pin-rivet - Page 1 of 2





**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Identification Code Color:

Blue

#### Fastener Length:

Between 3.660 inches and 3.680 inches

**Head Style:** 

Flush countersunk

Width Between Flats:

Between 0.158 inches and 0.161 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.755 inches and 0.760 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 3.120 inches and 3.130 inches

## Min. Tensile Strength (psi):

14000 pounds per square inch

## Thread Size:

0.375 inches

## Shear Strength:

21000 single pounds per square inch

### **Countersink Angle:**

100.0 degrees

### **Special Features:**

Grit blast top of head

### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-391-9665

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

