

View Online at <https://aerobasegroup.com/nsn/5320-01-391-9667>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Blue

**Fastener Length:**

Between 3.910 inches and 3.930 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.158 inches and 0.161 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.755 inches and 0.760 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 3.370 inches and 3.380 inches

**Min. Tensile Strength (psi):**

14000 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

21000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Grit blast top of head

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0