# NSN 5320-01-391-9669

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-391-9669



#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 1.097 inches and 1.117 inches

# Head Style:

Err-090

#### Head Height:

Between 0.130 inches and 0.140 inches

#### Width Between Flats:

Between 1.582 inches and 1.617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

#### Grip Length:

Between 1.102 inches and 1.112 inches

# Min. Tensile Strength (psi):

210000 pounds per square inch

# Thread Size:

0.375 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Nickel alloy 718

#### **Material Specification:**

Ams5662 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

258, cagec 73197 mfr ref single treatment response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-391-9669

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

