## NSN 5320-01-391-9674

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-391-9674 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.935 inches and 0.955 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches **Grip Length:** Between 0.450 inches and 0.505 inches Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-391-9674

Pin-rivet - Page 2 of 2



Fiig:

A528u0