

View Online at <https://aerobasegroup.com/nsn/5320-01-392-0073>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Natural

Fastener Length:

Between 0.753 inches and 0.773 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.433 inches and 0.443 inches

Min. Tensile Strength (psi):

1640 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

2540 double pounds per square inch

Countersink Angle:

100.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

88277-3d0086 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.