NSN 5320-01-392-0122

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0122 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 2.750 inches and 2.770 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.189 inches and 0.193 inches **Shank Diameter:** Between 0.436 inches and 0.437 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.881 inches and 0.888 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 2.120 inches and 2.130 inches Min. Tensile Strength (psi): 15900 pounds per square inch **Thread Size:** 0.438 inches **Shear Strength:** 28600 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-392-0122

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0