
NSN 5320-01-392-0124

Pin-rivet - Page 1 of 2





new Online at https://aerobasegroup.com/hsh/o

Thread Class:
За
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 4.160 inches and 4.180 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.158 inches and 0.161 inches
Shank Diameter:
Between 0.755 inches and 0.760 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.755 inches and 0.760 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 3.620 inches and 3.630 inches
Min. Tensile Strength (psi):
14000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
21000 single pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Grit blast top of head
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a

Unit Of Measure:

NSN 5320-01-392-0124

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

