NSN 5320-01-392-0129

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0129

Thread Class:
3a Thread Direction:
Right-hand Identification Code Color:
Blue Fractionar Longths
Fastener Length: Between 4.347 inches and 4.367 inches
Head Style: Flush countersunk
Width Between Flats: Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter: Between 0.7556 inches and 0.7604 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 3.807 inches and 3.817 inches
Min. Tensile Strength (psi):
14000 pounds per square inch Thread Size:
0.375 inches
Shear Strength:
21000 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Grit blast top of head, with color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unif
Specification Data:
73197-hlt453 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-392-0129

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A528u0