
# NSN 5320-01-392-0643

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 1.386 inches and 1.406 inches

# Head Style:

Err-090

## Head Height:

Between 0.080 inches and 0.090 inches

# Shank Diameter:

Between 0.2490 inches and 0.2495 inches

## Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.415 inches and 0.440 inches

## Lubrication:

Cetyl alcohol

# End Application:

C-17

## Grip Length:

Between 0.995 inches and 1.005 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

#### **Product Name:**

Pin-rivet, threaded

#### Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-392-0643

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

