## NSN 5320-01-392-0652

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-392-0652

| Fastener Length:   |
|--|
| Between 0.723 inches and 0.743 inches  |
| Head Style:  |
| Crown coutersunk greater than 135 degrees  |
| Shank Diameter:  |
| Between 0.1890 inches and 0.1895 inches  |
| Shank Style:   |
| Pin-rivet, multiple grooved  |
| Head Major Diameter:   |
| Between 0.331 inches and 0.335 inches  |
| Lubrication:   |
| Cetyl alcohol, specification 305, hi-shear corp  |
| Grip Length:   |
| Between 0.470 inches and 0.531 inches  |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Shear Strength:  |
| 95000 single pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Shelf Life:  |
| N/a  |

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A528u0