NSN 5320-01-392-0660

Pin-rivet - Page 1 of 1

A528u0



View Online at https://aerobasegroup.com/nsn/5320-01-392-0660

Fastener Length: Between 0.802 inches and 0.822 inches Head Style: Err-090 Shank Diameter: Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi): 160000 pounds per square inch
Head Style: Err-090 Shank Diameter: Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Shank Diameter: Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Shank Diameter: Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Between 0.2490 inches and 0.2495 inches Shank Style: Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Shank Style: Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Pin-rivet, multiple grooved Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Head Major Diameter: Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Between 0.446 inches and 0.451 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Grip Length: Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Between 0.470 inches and 0.531 inches Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
160000 pounds per square inch
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: