NSN 5320-01-392-0700

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0700

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.052 inches and 1.072 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3110 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.6287 inches and 0.6335 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.557 inches and 0.567 inches
Min. Tensile Strength (psi):
9200 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
14600 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas4006 assn standard single treatment response
Thread Series Designator:
Unif

Unjf

NSN 5320-01-392-0700

Pin-rivet - Page 2 of 2



Specification [)ata:
-----------------	-------

76823-03a073 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0