## NSN 5320-01-392-0702

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0702

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Identification Code Color:   |
| Blue   |
| Fastener Length:   |
| Between 1.052 inches and 1.072 inches  |
| Head Style:  |
| Flush countersunk  |
| Width Between Flats:   |
| Between 0.0791 inches and 0.0801 inches  |
| Shank Diameter:  |
| Between 0.1630 inches and 0.1635 inches  |
| Shank Style:   |
| Pin-rivet, straight, threaded  |
| Head Major Diameter:   |
| Between 0.3256 inches and 0.3304 inches  |
| Lubrication:   |
| Cetyl alcohol  |
| Grip Length:   |
| Between 0.745 inches and 0.755 inches  |
| Min. Tensile Strength (psi):   |
| 2180 pounds per square inch  |
| Thread Size:   |
| 0.164 inches   |
| Shear Strength:  |
| 4010 double pounds per square inch   |
| Countersink Angle:   |
| 100.0 degrees  |
| Special Features:  |
| Powder blast top of head, with color light blue on thread end.                                   |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator:  |
| Unjc   |
| Specification Data:  |
| 76823-03a073 manufacturers standard  |
| Shelf Life:  |
| N/a  |

## NSN 5320-01-392-0702

Pin-rivet - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0