NSN 5320-01-392-0703

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0703

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.323 inches and 1.343 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.933 inches and 0.943 inches
Min. Tensile Strength (psi):
5820 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
9300 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas4006 assn standard single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-392-0703

Pin-rivet - Page 2 of 2



S	pec	ific	cati	on	Data:

73197-hlt453 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0