## NSN 5320-01-392-0710

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0710

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.125 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.625 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.304 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Furnished w/ undersized thd dia; color light blue on thd end

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum alloy

## Surface Treatment Specification:

Hi-kote 1, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-392-0710

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

