
## NSN 5320-01-392-0712

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.062 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.102 inches and 0.112 inches

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.562 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.304 inches

## Shear Strength:

95000 single pounds per square inch

## **Special Features:**

Furnished w/ undersized thd dia

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Surface Treatment:

Aluminum alloy

## Surface Treatment Specification:

Hi-kote 1, cagec 73197 mfr ref single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-392-0712

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

