NSN 5320-01-392-0716

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0716

Thread Direction: Right-hand Identification Code Color: Blue Fastener Length: Between 1.127 inches and 1.147 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter:				
Right-hand Identification Code Color: Blue Fastener Length: Between 1.127 inches and 1.147 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Identification Code Color: Blue Fastener Length: Between 1.127 inches and 1.147 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Blue Fastener Length: Between 1.127 inches and 1.147 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Fastener Length: Between 1.127 inches and 1.147 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Between 1.127 inches and 1.147 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Width Between Flats: Between 0.0791 inches and 0.0806 inches				
Between 0.0791 inches and 0.0806 inches				
Shank Diameter:				
Shank Diameter:				
Between 0.1885 inches and 0.1895 inches				
Shank Style:				
Pin-rivet, straight, threaded				
Head Major Diameter:				
Between 0.3765 inches and 0.3813 inches				
Lubrication:				
Cetyl alcohol, specification 305, hi-shear corp				
Grip Length:				
Between 0.807 inches and 0.817 inches				
Minimum Yield Strength:				
2760 pounds per square inch				
Thread Size:				
0.190 inches				
Shear Strength:				
5380 double pounds per square inch				
Countersink Angle:				
100.0 degrees				
Special Features:				
Color light blue on thread end.				
Material:				
Titanium alloy uns r56400				
Material Specification:				
Ams4928 assn standard single material response or ams4967 assn standard single material response				
Surface Treatment:				
Aluminum				
Surface Treatment Specification:				
Hi shear spec. 294, cage 73197 mfr ref single treatment response				
Thread Series Designator:				
Unjf				

NSN 5320-01-392-0716

Pin-rivet - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

73197-hlt453 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0