## NSN 5320-01-392-0722

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0722

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 0.864 inches and 0.884 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0791 inches and 0.0801 inches
Shank Diameter:
Between 0.1630 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.3256 inches and 0.3304 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.557 inches and 0.567 inches
Min. Tensile Strength (psi):
2180 pounds per square inch
Thread Size:
0.164 inches
Shear Strength:
4010 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Powder blast top of head, with color light blue on thread end
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjc
Specification Data:
76823-03a073 manufacturers standard
Shelf Life:
N/a

## NSN 5320-01-392-0722

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0