NSN 5320-01-392-0723

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0723

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 2.375 inches and 2.395 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.1895 inches and 0.1930 inches
Shank Diameter:
Between 0.4365 inches and 0.4370 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.8812 inches and 0.8884 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 1.745 inches and 1.755 inches
Min. Tensile Strength (psi):
18900 pounds per square inch
Thread Size:
0.438 inches
Shear Strength:
28600 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Powder blast top of head, with color blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
76823-03a073 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-392-0723

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0