NSN 5320-01-392-0725

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0725 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.052 inches and 1.062 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches **Grip Length:** Between 0.5575 inches and 0.5675 inches Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 305, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:No

NSN 5320-01-392-0725

Pin-rivet - Page 2 of 2



Fiig:

A528u0