# NSN 5320-01-392-0726

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-392-0726



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Identification Code Color:

Blue

### Fastener Length:

Between 2.1775 inches and 2.1975 inches

**Head Style:** 

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.6286 inches and 0.6335 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 1.6825 inches and 1.6925 inches

Min. Tensile Strength (psi):

9200 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

14600 double pounds per square inch

## **Countersink Angle:**

100.0 degrees

**Special Features:** 

Powder blast top of head, with color light blue on thread end.

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Thread Series Designator:

Unjf

## **Specification Data:**

76823-03a073 manufacturers standard

Shelf Life:

N/a

# NSN 5320-01-392-0726

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

