## NSN 5320-01-392-0727

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0727

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 2.723 inches and 2.743 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.7556 inches and 0.7604 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 2.183 inches and 2.193 inches
Min. Tensile Strength (psi):
14000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
21000 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Powder blast top of head, with color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
76823-03a073 manufacturers standard
Shelf Life:
N/a

N/a

## NSN 5320-01-392-0727

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0