## NSN 5320-01-392-0768

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-0768 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.420 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style: Head Major Diameter:** Between 0.756 inches and 0.760 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.875 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.366 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Furnished w/ undersized thd dia; grit blast top of head, color light blue on thd end. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-392-0768

Pin-rivet - Page 2 of 2



Fiig:

A528u0