

View Online at <https://aerobasegroup.com/nsn/5320-01-392-1618>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.662 inches and 0.682 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.307 inches and 0.317 inches

Min. Tensile Strength (psi):

2750 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Special Features:

Caution, restricted usage, for repair work only, 0.0156 oversize part. Color white on thread end.

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Nas4006 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

76823-03a076 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0