NSN 5320-01-392-1621

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-392-1621

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.850 inches and 0.870 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.2016 inches and 0.2026 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.495 inches and 0.505 inches
Min. Tensile Strength (psi):
2750 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
5380 double pounds per square inch
Special Features:
Caution restricted usage, for repair work only, 0.0156 oversized. Color white on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas4006 assn standard single treatment response
Thread Series Designator:
Unif
Specification Data:
76823-03a076 manufacturers standard

NSN 5320-01-392-1621

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0