

View Online at <https://aerobasegroup.com/nsn/5320-01-392-1629>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.693 inches and 0.713 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2646 inches and 0.2651 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.245 inches and 0.255 inches

Min. Tensile Strength (psi):

5820 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Special Features:

Caution, restricted usage, for repair work only, 0.0156 oversize parts. Powder blast top of head, with color white on thread end.

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

76823-03a076 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0